Approved For Release 2003/08/11 :	CIA-RDP82400157	Hatabbo 17005.6	81	اكم
25X1	25X	1	Y,	95
CLASSIFICATION SECRET				\ `] 25X1
CENTRAL INTELLIGEN INFORMATION		REPORT NO.		20/1
HOME CONTRACTOR OF THE	recruit i	CD NO.		
COUNTRY Czechoslovakia		DATE DISTR.	10 Febr.	1950
SUBJECT Development of Weapons at the F (Bodenbach)Willitary Technical In		NO. OF PAGES	Ą.	
1 PLACE ACQUIRED		NO. OF ENCLS.	· 	
C1 DATE OF	A LIBRARY	SUPPLEMENT TO REPORT NO.	•	25X1
This decrees cureage independent appearing the rational deversing of the deviced cureage of the deviced rational deversion of the deviced ration of the deviced ration of the deviced ration of the contracts in any industrial and underviced record if produced ration of the opening ration of the opening record is produced by the appearance of the opening opening of the opening opening of the opening opening opening of the opening openi	THIS IS UNEVA	ALUATED INFORMAT	ION	
			25X1	_
and released against the targe the latter had come into sight to the pilot after being fired tail with brightly surning lum ignited at release. The proje circulated by an electro-magneti the aircraft carrying a transm jectile the receiving set. The propulsion was effected by alcohol aided by compres	. In order to the project incous discs contile was concerned by the bound of water, the bound of waters of	tile was fitted of powder which the formule from (short wave cooldy of the property of the property of the freediluted me releasing the	d at its h were the ntrol', -	
projectile, the pilot electric in the compressed-air valve, th rugm so that compressed air fl in the fuel container. As the fuel through the pipe conduit where it was ignited, the comp	nus perforation of the balloon expension the combones of the combones of the combones of the balloon is a balloon to the combones of the balloon is a balloon to the combones of the balloon is a balloon to the combones of the balloon is a balloon to the balloon	ng a tin diaph rubber balloon anded, it force bustion chambe and to horeby regrade and to horeby regrade to the second with the second with the second second second second the second s	eed.	
Bocument W. 665	Directo.	2. e 1	o the	
Class. Changed Auth.: HR 70-2 Date:		EXPLOITED	BY 🍎	
SECURITY INFO	RMATION			
CLASSIFICATION SHOREST	BUTION			25X1
ARM		regraded to	ONFIDE	NTIAL
Approved For Release 2003/08/11o:	ota i i	e to the		

Next Fig. .

25X1

-2-

CONFIDENTIAL

com ressed air was supplied from a built-in compressed air cylinder. Experiments against ground targets were made in late February and early in Parch 1949, in LACKY (P 49/S 22), Slovakia. Experiments on the Yugoslavian coast had also been arranged but due to the political situation did not take place. Only 3 of the 50 available projectiles at the Filitary Technical Institute in FORMOKLY have been fired.

The experiments were directed by staff captains Otto GROSS-TATE and REAL. The main experiments were done with the transmission sets and engines. An experimental transmitter for controlling the exhaust gases was installed. It was thought that original projectiles, Fentschel-298, were concerned, which were only tested and fitted with transmitters, each costing about 1 million Czech crowns. The rocket projectiles of this kind were not built at the FOYOVEY The bory Technical Institute.

According to rumors, these operations were to be transferred to the area 11 miles northeast of OLOMOUS (P40/185), probably STERNBERK (P 50/185) (Lunatic Asylum).)

2. Ockets with liquid propellants were being developed under the nonagement of Staff Capt. Otto CHOUREM and Liber FOLDWOR. Constructional designs were not available and only six experiments have been ade in the bunker of the Filitary-Jechnical Systitute, five of them failing.

A rocket motor similar to that used with the rocket projectile Tentschel-298 is concerned. The ignition was effected without a fuze, viz., by means of an anilin-like substance merging with nitric acid. For the experiments steel cylinders containing compressed air, cylinders with nitric acid, and special white cylinders with the anilinlike substance were used. A valve was opened with the Hentschel-298 rocket projectile, when the liquid with compressed air passed into the combustion chamber, the mixture causing an explosion; the gases escaped through a nowale.

3. Assisting rockets for airplane take-offs.

The take-off assisting rocket was first built for c-109 and was about 50 inches long, with a diameter about 51; inches. It was a steel tube with attachment books, fitted at the forward end with a stream-lined lug and at the rear with a nozzle. The propelling charge was a powder rod weighing about 50 lbs. Small strips of wood were fixed to its surface with small pins, and there was a 0.6-inch bore-hole for the passage of the rases in the middle of the nowder rod. Dehind the propelling charge a grate was attached. The powders were tested in the subterranean bunker. The chambers had a standard steel tube closed by a lid on one side, the apposite side being fitted with an exchangeable nozzle. The gas pressure was measured and the nozzle pressure and burning time were determined. The powder samples were later sent to STILL for the namufacture of charges.

	J 05V4
710 HE	2581

Approved For Rele	iãse 2003/08/11 : CIA-RDP82-00457R0042001 ;	70005-6
SECRET		

25X1

25X1

GENTRAL INTELLIGENCE AGENCY -ZONFIDENTIAL

The take-off assisting rockets were tested on "e-109 planes at the HBELY airfield.

The nanufacture of take-off rockets for Dakota planes was started in late Tarch 1949. They were said to be 6.6 feet long with a diameter of 15.78 inches.

4. Turbojet power units were built only in Czechoslovakia at the lilitary-Technical Institute at PODFOLLY, where the disassembled engines left by the Germans were put together again. This was formerly the case with the Juno engines which, after completion, were fitted into the e-262 plane.

| five RFF-003 organes were

being assembled under the direction of Oldrich TURTA, his two assistants Bohous TTATEA and Tyzen CA BOUT, and two mechanics of the LIBUREC Tilitary Specialist School for Lireraft Mechanics. These engines had been sent to LUTHATY for testing prior to Christmas 1948 and had been taken over by Tng. MULMTA, had been returned to TODECLY, then shipped back to LETHATY for installation in planes after the wing attachments had been fixed to them. It was intended to install them in Czech type aircraft.

The hourly fuel consumption of this HY-003 power unit was 258 callons. The mixture was pure petroleum with a small quantity of aviation oil. The engines were started by a middle casoline orgine, which started the main shaft with the compressor and the turbine wheel. The about 700 r.p.m., the fuel was forced up by the injection nozzles and ignited in the combustion characters.

25X1 Corrient:

25X1

a. It has been repeatedly reported that in a section of the illitary sechnical Institute in PODMOKLY research work is done on guided missiles. The present report confirms these statements.

b. Dating from October 1946, other information is available that work had been resumed in the subterranean plant in PODMOKLY, which was built for the manufacture of V-weapons. This plant was located between the freight station and the libe liver on the premises of the former etallwarks ".A. Lange (now belonging to the mationalized plant of Poehmische Tetallwalzwerke (Bohemian etal Tilling orks) and the TG (now belonging to the CKD). The type of V-weapons to be manufactured there is not known. The existing suided missiles indicate that probably part of this production was treasferred to BODE TACE.

c. It seems credible in the case of the reported guided missiles, that it is not the question of posture production, but of the assembly and testing of parts manufactured during the man, as Czechoslovakia lacks the required technical specialists. In the case of the guided missiles it probably reads Tentschel 293 instead of Tentschel 298 as, according to the description, guided missiles for use against ground targets are concerned. Iso the Ts-298 was propelled by a two-stage porder rocket, but the Ts-295 rocket was made for different limits of propulsion (methanol liquefied 02 or an omilin liquid as contioned in para 2).

25X1

Approved For Release 2003/08/11 : CIA-RDP82-00457R0042001	70005-6	

25X1

25X1

ACENTRAL INTELLIGENCE AGENCY

CONFIDENTIAL

- d. There is a large troop training grounds in MALAGKY where aircraft and ground meanons are tested.
- e. large-scale tests of aircraft meapons had been made in Yugoslavia by Czechoslovakia before the mar, especially in CATARO or the larst region mear LOSTAR

therefore, were provided for executests in Vugoslavia, but not for Yugoslavia).

- f. The use of rockets as take-off assisting devices and flight accelerators (flight boosters) was demonstrated, on aviation pay, in WOOM (September 1947) by the Czech ir Force. These statements are therefore considered correct.
- g. The statements on the assembly of turbojet power units are also considered correct. The fact that, from now on, Czechoslovekia will use pure petroleum as fuel for turbojet power units was not known.
- h. In REICHENBACH/LIBEREC there is the School for Flight Mechanics.

HONE .